

TECH LINE COATINGS, INC.



26844 ADAMS AVE. ♦ MURRIETA, CA 92562 ♦ USA

Phone 1-972-775-6130

♦ Fax 1-951-461-9658

www.techlinecoatings.com

COATING PROPERTIES

PRODUCT: Turbo X

COLOR: Blue

APPLIED FILM THICKNESS: .0005" to .0015"

HRC (Equivalent Rockwell C Scale): N/A

ADHESION (Tape Test ASTM D 3330):

PENCIL HARDNESS TEST:

IMPACT TEST (ASTM D 2794 2 lb. Weight): N/A

FLEXIBILITY/ BENDING ADHESION: Good

THERMAL TEMPERATURE RESISTANCE: Maintains adhesion at base metal temp. in excess of 2000f. intermittent & over 1600f. constant. Survives cyclic heating & cooling.

THERMAL SHOCK TESTING: Excellent

SALT SPRAY RESISTANCE: N/A

CORROSION TEST DATA: Excellent

PHYSICAL PERFORMANCE (Wear & Load): N/A

ACCEPTABLE SUBSTRATES FOR APPLICATION: All metals except Magnesium

ELECTRICAL PROPERTIES: N/A

CHEMICAL RESISTANCE: Excellent

IMPORTANT: The technical information herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of this product. NO WARRANTY EXPRESS OR IMPLIED, IS MADE INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE WHICH ARE SPECIFICALLY EXCLUDED.

READ THE MATERIAL SAFETY DATA SHEET BEFORE USE.